

# Saab 9<sup>3</sup> 2003+ Aux-in Cable Dealer Installation Instructions

These instructions are intended to be given to your Saab Service Technician.

If you would like to install this yourself, please visit us on the web at [www.etadyne.com](http://www.etadyne.com) for full instructions.

-Enable Aux-In using the Tech II:

1. Add/Remove
2. Then add module
3. Then scroll down select "ICM"
4. It will show what the system already has... then scroll down & select "Aux Input"
5. Then add it, then system reboots etc, stereo goes on then off
6. Test it: Cycling the SRC button on steering wheel should yield a "AUX" source on the SID.

-Remove & unplug HVAC faceplate.

-Remove EHU to expose the connectors in back. ⚠ Take care not to damage the fibre-optic cables by bending them too much.

-Remove center console side trim attachment screw on right side.

-Remove two right side center console side trim panels.

-Route cable through corresponding hole in armrest, down to floor, across floor of center console, up through center stack, and up to EHU. Assemble shroud to plug.

-Connect cable to back of EHU. It will only go in 1 location.

-Test connection by hooking up a source & verifying sound is coming out of left & right speakers by using the Balance control.

-Secure cable using included cable ties so it does not wander. ⚠ Pay special attention to ensure cable will not interfere with operation of parking brake.

-Reassemble vehicle.